EC-TYPE EXAMINATION CERTIFICATE

The following model of Personal Protective Equipment has been subjected to an EC-type examination in accordance with the article 10 of the PPE Directive (89/686/EEC) and has been shown to satisfy the relevant provisions of the Directive.

Certificate N° **0075/1714/162/05/17/0597**

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : **Vicsa Safety Comercial Limitada**
Panamericana Norte 5151, Conchalí, Santiago
Chile

Distributor : /

Description

PPE Type : ***protective glove against mechanical risks***

Product reference : **MULTIFLEX MULTIPROPOSITO**

Glove description : **10 gauge yellow polyester coated latex of high dexterity**

This product is a category II.

Available sizes : **10/L(SAP:301000780052)**

Pictures :





Reference standard :	Levels of performance / class of protection
EN 420:2003+A1:2009	-
EN 388:2016	**2 1 4 3 X**
The levels of performance have been measured on the palm	**« X » means that the test hasn't been performed ; no protection is required**

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EC-type examination and information given on the product are detailed in the manufacturer's technical file index 01 dated from MAY 2017

NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the CE type approval certificate (change of adress, change of company status) should be brought to the attention of the notified body in accordance with law n° R.4313-38 of the French Code of Work

Issued in Lyon by

Lionel Gaudillere
PPE certification manager

Date of issue : May 10th 2017

CE MARKING DEPARTMENT CTC NB 0075

In application of the Directive 89/686/EEC of the 21th December 1989, concerning the alignment of member state legislation relating to personal protective equipment and in application of relevant requirements of the french labor code, providing by the transcription of these Directive into french regulation.

www.ctcgroupe.com
cemarking@ctcgroupe.com
CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

NOTIFIED BODY CTC 0075 CE Marking

Vicsa Safety Comercial Limitada

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	**MULTIFLEX** **MULTIPROPOSITO**
Technical file index	:	**01**
Last update	:	**MAY 2017**

IDENTIFICATION

Reference of the product :	:	MULTIFLEX MULTIPROPOSITO
Basic model		
Technical file index :	:	01
Last update :	:	MAY 2017

Manufacturer :

Vicsa Safety Comercial Limitada

Panamericana Norte 5151, Conchalí, Santiago

Chile

tel : +56 223073200

fax :

GLOVE DESCRIPTION

Glove description :

10 gauge yellow polyester coated latex of high dexterity

type of coating finish : crinckle

Visual description :



Field of use, Risks against which the product protects :

mechanical risk

Available sizes :

Minimum length of glove (mm)	Sizes
260	10/L(SAP:301000780052)

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		BLACK	LATEX	450G/M2	10gauge/ inch	0.1-0.15cm
		YELLOW	POLYESTER	475G/M2	10gauge/ inch	
Back		YELLOW	POLYESTER	475G/M2	10gauge/ inch	
Lining						
Cuff		YELLOW	POLYESTER/ ELASTIC	475G/M2	10 gauge/ inch	
Binding		BLACK	POLYESTER			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes
Chromium VI lower than the detection limit : conform
Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	2
Blade cut resistance	1
Tear strength resistance	4
Puncture resistance	3
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm
« X » means that the test hasn't been performed ; no protection is required

TEST REPORTS

Laboratory	CTC	Other
EN 420	SH60528-14 S160909658_1 S170200852_1	
Azo	SH60528-14 S160909658_1	
EN 388	S160909658_1 S170200852_1	
OTHER	S160909658_1(TIN, CAD, PAHs) S170200852_1(DMFu)	

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :
Logo CE
Glove's reference : MULTIFLEX MULTIPROPOSITO
Size indicator
Pictograms related to risks against which protection is offered with performance levels
Information pictogram

Marking example :



Method of marking on the glove :

heat stamp logo on the back of the glove, one sewing label each glove

Packaging :

12pairs/polybag, 60pairs/carton

MEANS OF CONTROL

According to ISO 9001



bsi.

By Royal Charter

Certificate of Registration

QUALITY MANAGEMENT SYSTEM - ISO 9001:2008

This is to certify that:

山东登升劳保用品有限公司
77842183-4
中国
山东省
乌密市
朝阳街道
鸠哥庄社区
鸠肃路西侧
邮编：261502

Holds Certificate No: FM 548437

and operates a Quality Management System which complies with the requirements of ISO 9001:2008 for the following scope:

The manufacture of coated working and safety gloves.
搅胶类劳保手套的生产。

For and on behalf of BSI:

Pietro Foschi - Strategic Delivery Director

Originally registered: 06/08/2009 Latest Issue: 28/01/2015 Expiry Date: 15/02/2018

Page: 1 of 1

...making excellence a habit.™

The certificate was issued electronically and remains the property of BSI and is bound by the conditions of contract.
[illegible]
[illegible] requirements may be obtained by consulting the organization.
[illegible]

Information and Contacts: BSI, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP. Tel: + 44 345 080 9000
BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
BSI Management Systems Certification (Beijing) Co., Ltd
Rm. 2008 East Ocean Center, No. 24A Jianguomenwai Street, Beijing 100004, P. R. China Tel: +86 10 8507 3000
A Member of the BSI Group of Companies.

INSTRUCTION FOR USE

Vicsa Safety Comercial Limitada
Panamericana Norte 5151, Conchalí, Santiago
Chile
Glove reference : MULTIFLEX MULTIPROPOSITO

Available sizes : 10/L(SAP:301000780052)

Glove description :

10 gauge yellow polyester coated latex of high dexterity

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.
It has been subject to a CE type Examination performed by :

C.T.C. (OO75)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5
Moreover, this glove has been designed for the following applications :

Application :
Mechanical hazard - EN 388



2 1 4 3 X
Levels of performance

Abrasion resistance	2	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	4	(on 4 maxi)
Puncture resistance	3	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » means that the test hasn't been performed ; no protection is required

Protection limit :

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.
The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.
This glove shall not be in contact with fire.
Users should be warned that gloves should not be worn when there is a risk of entaglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.